



Technical Data Sheet:

METHANOL, (Methyl Alcohol)

Specific Gravity, 20°/20°C (E-346)
Distillation at 760 mm Hg, °C (D-1078)
Purity, % by wt
Nonvolatile, mg/1000 ml (D-1353)
Acidity, % by wt, as Acetic Acid (D-1613)
Acetone, % by wt (D-1612)
Carbonizable Substances, Pt-Co (E-346)
Permanganate Test at 15°C, minutes (D-1363)
Water, % by wt (E-346)
Color, Pt-Co (D-1209)
Hydrocarbons (D-1722)

SPECIFICATIONS

0.791 - 0.793
1.0 range (to include 64.6 ± 0.1)
99.85 min
8 max
0.003 max
0.003 max
30 max
60 min
0.10 max
5 max
Pass Test

SHIPPING DATA:

Pounds per Gallon, 20°C
Kg per Liter, 20°C
Flash Point, °F (T.C.C.)
DOT Label Required
DOT Identification No.

6.59
0.79
54
Flammable Liquid
UN 1230

Code: 20297 (BULK)
C.A.S. No.: 67-56-1
() Indicates ASTM Test Method
1709



112 Grace Ave
Clontarf, MN 56226

1200 29th Ave NE
Sauk Rapids, MN 56379

530 E Amidon St
Sioux Falls, SD 57104



1.800.992.8815



320.251.2131



orderdesk@chamberlainoil.com